



Sicad South Africa (PTY) LTD

20 Cocopan Crescent, Driehoek, Germiston
Gauteng, South Africa
Tel: +27 11 873 1311 FAX: +27 11 873 2396
Web: www.eurocel.it

PRODUCT INFORMATION

EUROCEL PVC 330 TAPE

DESCRIPTION

Single sided packaging tape.

PRODUCT DATA

Backing	0.033 PVC film
Adhesive	Dry natural rubber and resins; clear; buff; white.

	Unit	Average Value	Method
Total thickness	mm	0.052 (clear) – 0.052 (buff) – 0.054 (white)	PSTC 133
Adhesion to steel	N/25mm	3.5	PSTC 101
Tensile strength MD	N/25mm	125	PSTC 131
Elongation at break	%	60	PSTC 131
Temp. Resistance	°C	60°C	=

APPLICATION

Single sided carton sealing tape; suitable for use on standard and most recycled cartons; available in clear; buff; and white versions.

Features	Benefits	
Dry natural rubber and resins adhesive	<ul style="list-style-type: none"> ✓ Good adhesion in several applications ✓ Performing even at low temperature* <p><i>*Suggested application at room temperature over 15°C before storing sealed items at lower temperature.</i></p>	<ul style="list-style-type: none"> ✓ Suitable for use on most recycled cartons
PVC backing	<ul style="list-style-type: none"> ✓ Well adaptable to uneven shapes ✓ Good elongation 	<ul style="list-style-type: none"> ✓ No noise unwinding

CONDITIONS OF USE AND CONFORMITY

Product shelf life and storage: 12 months; based on the product being stored at 15°C to 25°C with max. relative humidity of 65% out of direct sunlight. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature is lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.

