

Man-machine dialogue

- Ø 22 mm Push Button valves : panel mounting
- Ø3/2 NO or NC ; modular assembly (with upto 3 valves per head) Complete range of operating heads
- Pneumatic and or electrical signals



Operating information

Push Buttons

Working pressure	
PXB-B3..	1 to 9 bar
PXV-...	1 to 8 bar
Working temperature	-15 °C à 60 °C
Flow PXB-B3..(sivalent ISO 6358)	Qmax. = 60 l/min
pneumatic connection	Ø4 mm push - in

Spring return push buttons valves

Symbol	Flow	Order Code	Symbol	Flow	Order Code	Symbol	Flow	Order Code
	50 l/min	PXB-B3111BA2		50 l/min	PXB-B3111BA3		50 l/min	PXB-B3111BA4
		Black - 1 valve NC			Green -1 valve NC			Red - 1 valve NC

Spring return push buttons

Symbol	Flow	Order Code
	50 l/min	PXB-B3111BC2
		Black - Spring return 1 valve NC

Push - Pull buttons

Symbol	Flow	Order Code
	50 l/min	PXB-B3111BT4
		Red - Push - Pull 1 valve NC

Selector switches

Symbol	Flow	Order Code
	50 l/min	PXB-B3111BD2
		Black - 2 Positions 1 valve NC

Pneumatic valves with additional electrical contacts

Symbol	Flow	Order Code	Symbol	Type of contact	Order Code	Symbol	Type	Order Code
	50 l/min	PXB-B3911		Normal open	ZBE-101		Mounting	ZB4-BZ009
		NC			NO			
	50 l/min	PXB-B3921		Normal closed	ZBE-102			
		NO			NF			

Push buttons

Spring Return			Mushroom Head Spring Return			Standard Selector Switches - Black		
	Colour	Order Code		Colour	Order Code		Function	Order Code
	Black	ZB4-BA2		Black	ZB4-BC2		2 position	ZB4-BD2
	Green	ZB4-BA3		Green	ZB4-BC3		3 position	ZB4-BD3
	Red	ZB4-BA4		Red	ZB4-BC4			
Flush			Ø40 mm Spring return			Handle 4°		

Visual Indicators

Symbol	Colour	Order Code
	Green	PXV-F131
	Red	PXV-F141
	Yellow	PXV-F151
	Blue	PXV-F161
	White	PXV-F111