


Vinyl-insulated Ring Terminals

Cable size:0.5 ~ 1.5mm² (A.W.G.22 ~ 16) Max current:Imax=19A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:0.75mm

ITEM NO	USA screw	Screw dia.d2(mm)	Dimension(mm)					Color
			B	L	F	H	Dp	
RV 1.25-3	#4	3.2	5.7	17.8	4.95	10.0	4.3	red
RV 1.25-3.5 S	#6	3.7	5.7	17.8	4.95			
RV 1.25-3.5 M	#6	3.7	6.6	20.1	6.3			
RV 1.25-3.5 L	#6	3.7	8.0	21.5	7.0			
RV 1.25-4 S	#8	4.3	6.6	20.1	6.3			
RV 1.25-4 L	#8	4.3	8.0	21.5	7.0			
RV 1.25-5 S	#10	5.3	8.0	21.5	7.0			
RV 1.25-5 L	#10	5.3	9.8	23.0	8.5			
RV 1.25-6 S	1/4	6.4	9.8	23.0	8.5			
RV 1.25-6 L	1/4	6.4	11.6	27.5	11.1			
RV 1.25-8	5/16	8.4	11.6	27.5	11.1			
RV 1.25-10	3/8	10.5	13.6	31.6	13.9			
RV 1.25-12	1/2	13.0	19.2	36.0	16.5			



Cable size:1.5 ~ 2.5mm² (A.W.G.16 ~ 14) Max current:Imax=27A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:0.8mm

ITEM NO	USA screw	Screw dia.d2(mm)	Dimension(mm)					Color
			B	L	F	H	Dp	
RV 2-3	#4	3.2	6.6	17.8	4.3	10.0	4.9	blue
RV 2-3.5 S	#6	3.7	6.6	17.8	4.3			
RV 2-3.5 M	#6	3.7	6.6	20.0	6.5			
RV 2-3.5 L	#6	3.7	8.5	22.5	7.75			
RV 2-4 S	#8	4.3	6.6	20.0	6.5			
RV 2-4 L	#8	4.3	8.5	22.5	7.75			
RV 2-5 S	#10	5.3	8.5	22.5	7.75			
RV 2-5 L	#10	5.3	9.5	22.5	7.25			
RV 2-6	1/4	6.4	12.0	27.6	11.0			
RV 2-8	5/16	8.4	12.0	27.6	11.0			
RV 2-10	3/8	10.5	14.6	31.2	13.9			
RV 2-12	1/2	13.0	19.2	36.5	16.5			

Cable size:2.5 ~ 4mm² (A.W.G.14 ~ 12) Max current:Imax=37A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:1.0mm

ITEM NO	USA screw	Screw dia.d2(mm)	Dimension(mm)					Color
			B	L	F	H	Dp	
RV 3.5-4	#8	4.3	8.0	24.5	7.7	13.0	6.2	black
RV 3.5-5 S	#10	5.3	8.0	24.5	7.7			
RV 3.5-5 L	#10	5.3	12.0	27.9	7.7			
RV 3.5-6	1/4	6.4	12.0	27.9	7.7			
RV 3.5-8	5/16	8.4	15.0	34.0	14			
RV 3.5-10	3/8	10.5	15.0	34.0	14			

Cable size:4 ~ 6mm² (A.W.G.12 ~ 10) Max current:Imax=48A Temperature:75°C

Material:Purple copper Sheath:PVC Thickness:1.0mm

ITEM NO	USA screw	Screw dia.d2(mm)	Dimension(mm)					Color
			B	L	F	H	Dp	
RV 5.5-3	#4	3.2	7.2	21.4	5.9	13.0	6.7	yellow
RV 5.5-3.5	#6	3.7	7.2	21.4	5.9			
RV 5.5-4 S	#8	4.3	7.2	21.4	5.9			
RV 5.5-4 L	#8	4.3	9.5	25.5	8.3			
RV 5.5-5	#10	5.3	9.5	25.5	8.3			
RV 5.5-6	1/4	6.4	12.0	31.5	13.0			
RV 5.5-8	5/16	8.4	15.0	33.7	13.7			
RV 5.5-10	3/8	10.5	15.0	33.7	13.7			
RV 5.5-12	1/2	13.0	19.2	38.1	16.0			