



adhesive tapes catalogue

DS FOAM 3.0

Fixing, mounting and fastening




3.0 foam, medium adhesion

Thick double sided foam tape suitable for mounting dispensers, numbers plates and other general purpose applications. Excellent adhesion and holding power.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Foam	Acrylic adhesive	White (white paper liner)	3.000 mm	> 19.6 N/25mm	\	\	60°C

TB7772 TOUGH BOND WHITE

Fixing, mounting and fastening




Foam like solvent acrylic adhesive

Film of viscoelastic adhesive tape. The adhesive bonds to a wide range of material including metal and glass. Most substrates are best prepared by cleaning with 50:50 mixture of isopropyl alcohol (IPA) and water prior to applying.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Foam	Solvent acrylic	White (MOPP red liner)	1.100 mm	49 N/25 mm (90° peel adhesion)	50 N/25mm	\	150°C

TB7774 TOUGH BOND TRANSPARENT

Fixing, mounting and fastening





Foam like solvent acrylic adhesive

Film of viscoelastic adhesive tape. The adhesive bonds to a wide range of material including metal and glass. Most substrates are best prepared by cleaning with 50:50 mixture of isopropyl alcohol (IPA) and water prior to applying.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Foam	Solvent acrylic	Transparent (MOPP red liner)	1.000 mm	49 N/25 mm (90° peel adhesion)	\	\	80°C

TB7776 TOUGH BOND GREY

Fixing, mounting and fastening



Foam like solvent acrylic adhesive

Film of viscoelastic adhesive tape. The adhesive bonds to a wide range of material including metal and glass. Most substrates are best prepared by cleaning with 50:50 mixture of isopropyl alcohol (IPA) and water prior to applying.

BACKING	ADHESIVE	COLOUR	TOTAL THICKNESS	ADHESION	TENSILE STRENGTH	ELONGATION TO BREAK	TEMPERATURE RESISTANCE
Foam	Solvent acrylic	Grey (MOPP red liner)	1.100 mm	69 N/25 mm (90° peel adhesion)	45 N/25mm	\	90°C