

**PRODUCT**  
SOLOMON



SOLDERING STATION (11)

- [SL-10](#)
- [SL-20](#)
- [SL-20 ESD](#)
- [SL-20CMC](#)
- [SL-30](#)
- [SL-30 ESD](#)
- [SL-30CMC](#)
- [SL-30CMCESD](#)
- [SR-976](#)
- [SR-976ESD](#)
- [SR-998](#)

DESOLDERING STATION (3)

SUCKER TIN PUMP (4)

HOT AIR SMD REWORK STATION (1)

SOLDERING IRON (22)

SOLDERING IRON STAND (3)

STAINLESS TWEEZERS (3)

RHINESTONE APPLICATOR (1)

SPECIAL SOLDERING TIP (1)


**PRODUCT LINE**

PRODUCT LINE > SOLDERING STATION(11) > SL-30

**SL-30**



**SPECIFICATIONS**



<b>Voltage</b>	110/120V AC or 220/240 V AC	
<b>Power consumption</b>	48W	
<b>Temp.setting range</b>	160°C~480°C 320°F~900°F	
<b>Heater Operating Voltage</b>	24V AC	
<b>Size</b>	<b>Handpiece</b>	203mm
	<b>Station</b>	L170:W 116:H96 (mm)
<b>Weight</b>	1940g	
<b>Station-Handpiece cordlength</b>	115 cm	
<b>AC Power cord</b>	2pin or 3pin plug 180cm	
<b>Packing Measure</b>	8 pcs CUFT 1.77'	

**DESCRIPTION**

**ADJUSTABLE TEMPERATURE CONTROLLED SOLDERING STATION**

The temperature on the panel of the SL-30 temperature-control soldering iron station is displayed digitally with the adjustment range from 160C to 480C.

The digitally displayed temperature on the panel can be adjusted to SET thus setting all the required temperatures for operation and such a setting is very accurate.

**CHARACTER**



EUROPE STANDARD



AMERICA STANDARD



Copyright 2007 Somy Roong Industrial Co.,Ltd. ALL RIGHTS RESERVED.  
 Address:4F.No.138.Chung Cheng Rd.,Chung Ho City,Taipei Hsien, Taiwan R.O.C.  
 TEL:886-2-2244-6128 / FAX:886-2-2244-6803  
 E-mail:solomon@soldering.com.tw / somyroong@soldering.com.tw