



T820

- DIY
- Large LCD display
- Continuity
- Diode

Feature	Parameter	Accuracy
DC Voltage (V)	200mV, 2, 20, 200, 600V	±0.5% + 4 Digit
AC Voltage (V)	200, 600V	±1.2 % + 10 Digit
DC Current (A)	200µ, 2mA, 20mA, 200mA,10A	±1.5 % + 3 Digit
Resistance (Ω)	200, 2k, 20k, 200k, 20MΩ	±1.2% + 4 Digit
Counts	3 -1/2 Digits	1999 Counts

CAT III / 600V

Model Specification



T835

- DIY
- Continuity
- Diode
- Data hold

Technical Overview

Feature	Parameter	Accuracy
DC Voltage (V)	200mV, 2, 20, 200, 600V	±0.5% + 4 Digit
AC Voltage (V)	200, 500V	±1.2 % + 10 Digit
DC Current (A)	200mA, 2mA, 20mA, 200mA,10A	±1.0 % + 2 Digit
Resistance (Ω)	200, 2k, 20k, 200k, 20MΩ	0.8% + 10 Digit
Temperature (°C)	-20°C to 1000°C	±1.0 % + 3 Digit
Counts	3 -1/2 Digits	1 999 Counts

CAT III / 600V

Model Specification

Power Source 1 x 9V Battery

Standard Accessories Temp Probe **TBMTEMP**PROBE

T1300H

Feature	Parameter	Accuracy
DC Voltage (V)	200mV, 2, 20, 200, 500V	±0.5% + 2 Digit
AC Voltage (V)	200, 500V	±1.2% + 10 Digit
DC Current (A)	2mA, 20mA, 200mA,10A	2mA-200mA ±1% +2 Digit
Resistance (Ω)	200, 2k, 20k, 200k, 20MΩ	±1% + 5 Digit

Power Source 1 x 9V Battery

Diode		$\pm 1\text{mV}$
Counts	3 -1/2 Digits	1 999 Counts

- Backlit
- Diode
- Continuity
- Data hold
- Electronic



Technical Overview

Model Specification

CAT III 600V