

Thermometer SERIES



THERMOMETER, 4 channels

Model : TM-903A

- * 4 channels input.
- * Thermocouple type J & type K.
- * -100 to 1300 °C, max. 0.1 °C/ 0.1 °F.
- * RS-232/USB, Hold, Record (Max., Min.).

THERMOMETER, 4 channels, 4 display

Model : TM-946

PT 100 ohm TEMPERATURE PROBE

Model : TP-100

- * The exclusive Pt 100 ohm precision Temp. probe for TM-907A, TM-917, TM-917HA, TM-2000, TM-936.
- * Sensor type : Pt 100 ohm.
- * Range : -50 to 400 °C.



TP-01 TP-02A TP-03 TP-04

TYPE K TEMPERATURE PROBE

TP-01 : -40 to 250 °C, Naked-bead.

TP-02A: -50 to 900 °C, 3.2 mm Dia. x 10 cm.

TP-03 : -50 to 1000 °C, 8 mm Dia. x 10 cm.

TP-04 : -50 to 400 °C, Surface probe.



THERMOMETER, 2 in 1

Model : TM-936

- * Type K/J/E/T : -100 to 1300 °C, max. 0.1 °C/0.1 °F.
- * Type R : 0 to 1700 °C, 1 °C/ 1 °F.
- * PT 100 ohm : -200 to 800 °C, max. 0.1 °C/0.1 °F.
- * RS-232/USB, Hold, Record (Max., Min.).



DUAL THERMOMETER, RS-232

Model : TM-906A

- * μ -P circuit, LCD with display unit.
- * Range : -200 to 1370 °C.
- * Max., Min., Memory recall button.
- * °C/°F, 0.1°/1°, T1, T2, T1-T2.
- * Size : 180 x 72 x 32 mm. RS-232/USB.



TWO CHANNEL THERMOMETER, pocket type

Model : TM-924C, TM-924F

- * T1, T2, Type K thermocouple, -50 to 1300 °C.
- * TM-924C : °C, 0.1 degree/1 degree.
- * TM-924F : °F, 0.1 degree/1 degree.
- * Data hold, LCD display with back light.
- * DC 9V (006P) battery or DC 9V adapter in.



PRECISION 0.01 degree THERMOMETER

Model : TM-917

- * Pt 100 ohm: -199.99 °C to 850 °C, + Type J/K/R/E/T
- * 0.01/0.1 degree, Memory, °C/°F, RS-232/USB.

PRECISION 0.01 degree THERMOMETER

Model : TM-907A

- * Pt 100 ohm : -199.99 °C to 850 °C, high accuracy.

PT 100 ohm TEMP. PROBE

Model : TP-100



DUAL THERMOMETER

Model : TM-916

- * μ -P circuit, LCD with display unit.
- * Range : -200 to 1370 °C.
- * Max., Min., Memory recall button.
- * °C/°F, 0.1°/1°, T1, T2, T1-T2.
- * Size : 180 x 72 x 32 mm.



DUAL CHANNEL THERMOMETER

Model : TM-914C, TM-914F

- * -40 to 1200 °C (TM-914C)
- * -40 to 2000 °F (TM-914F)
- * Type K, dual channel, pocket size.
- * Size : 131 x 70 x 25 mm.